

Target group



 Ethernet for Control Automation Technology

Motors, actuators, sensors


Real time data

Hardware compatible












Medium



100 Mbit/s EtherCAT

Min. telegram length (0...46 byte user data)* = 6.08 μs Max. telegram length (1,500 byte user data)* = 122.40 μs

- 100BASE-TX
- Vast choice of components



*incl. Preamble and VLAN-Tag

1 Gbit/s EtherCAT. G

Min. telegram length $(0...46 \text{ byte user data})^* = 0.58 \mu s$ Max. telegram length $(1,500 \text{ byte user data})^* = 12.24 \mu s$

- 1000BASE-T
- Integration of data-intensive devices
- Very high bandwidth



*incl. Preamble and VLAN-Tag

10 Gbit/s EtherCAT G10

Min. telegram length $(0...46 \text{ byte user data})^* = 0.06 \mu s$ Max. telegram length $(1,500 \text{ byte user data})^* = 1.22 \mu s$


- 10GBASE-T
- Integration of EtherCAT G segments
- Ultimate bandwidth



*incl. Preamble and VLAN-Tag

Functionality

- Ethernet protocol
- Slave only responds
- Internal clocking in slaves
- On the fly



EtherCAT Master EtherCAT Master Branch Branch Branch ECAT-2513 **▲** Daisy chaining connection **▲** Convert to branching connection

Topology

• Flexible

• Full-Duplex

Automatic link detection



7 Layers

EtherCAT®

7 - Application Layer (AL)

6 - Presentation Layer


5 - Session Layer

4 - Transport Layer

3 - Network Layer

2 - Data Link Layer (DL)

1 - Physical Layer (PL)



EtherCAT® Physical Layer

Category	Ether CAT(control automation technology)	Ethernet/IP (Industrial protocol)	PROFINET (Process field network)
Definition: Communication protocol for industrial ethernet network	Master-slave protocol which is high speed and deterministic while processing data	Uses the normal TCP from ethernet but works on level 5,6 and 7 of OCI model to exchange data	Designed to exchange data and use common ethernet for its communication medium
Features	 Processes on the fly Cycle time up to 100micro seconds High bandwidth and low latency and jitter No collisions of data Flexible topology and no hubs and switches 	 Needs to ingest data and process Cycle times up to 10ms Lower bandwidth, higher latency and jitter Requires hubs and switches Not adapted to data collision 	 Precise cyclic time(31.25 microseconds) due to direct transfer to ethernet fram Requires switches, sensors Real time and Isochronous time Coexists and integrates
Application	Often used in robotics, semiconductor manufacturing, machine control etc	Cannot be used for high-speed applications thus very common to use for data acquisition, diagnostics etc	used for automobile automation, manufacturing etc

Limitations


Can only have one master.


ASIC needed for the slave unit.

Market share and popularity

- Market research
- Surveys and feedbacks
- Sales data
- Collaboration with companies and conferences for insight

2022 Industrial Network Market Shares according to HMS Networks









Sources

- https://www.rtautomation.com/technologies/ethercat/ (02.10.23)
- https://www.anybus.com/technologies/industrial-ethernet/ethercat
- https://www.analog.com/en/products/landing-pages/001/introduction-ethercat-fieldbus.html (09.10.23)
- https://www.elprocus.com/ethercat/ (09.10.23)
- https://infosys.beckhoff.com/english.php?content=../content/1033/ax2000 -b110/html/bt ec wiring.htm&id=6164175449606470319 (09.10.23)
- https://www.icpdas.com/en/product/guide+Industrial Communication+E therCAT+Junction and Converter (22.10.23)
- https://www.ethercat.org/en/why use ethercat.htm (22.10.23)
- https://www.ethercat.org/en/technology.html (22.10.23)