



FIXED LIGHT
(SA)

N|TECH 0.7



- High performance passive design
- Fantastic energy saving
- Large secure glazed areas
- Custom-made shapes and sizes
- Solid construction
- Great weather performance



Enhanced security



Safe for children



Sound reduction



Energy saving



Optional aluminium cladding



■ Aluminium clad corner section, viewed externally

FIXED LIGHT

(SA)



■ *NorDan's fixed light window, interior view*



Custom angled shapes available to suit your design.



Fixed light exterior view, standard timber



Fixed light exterior view, aluminium clad timber

CONSTRUCTION

Fixed lights are available glazed or with insulated panels allowing for inclusion of non-vision panels.

INSULATED FRAME

A layer of insulation is laminated into the 105mm deep frame offering a solid, high performance construction. Timber is double vacuum impregnated for protection and has full PEFC chain of custody accreditation.

TRIPLE GLAZED SEALED UNIT

Improved energy saving unit contains low emissivity glass and argon filled cavities: 4E5mm + 16mm Argon +4mm + 16mm Argon + ES4mm. Other glazing options are available. Warm edge technology is employed in the spacer bars to improve the thermal efficiency of the sealed unit.

OPTIONS

OPTIONAL ALUMINIUM CLADDING

Aluminium cladding increases the life-span of the window and also greatly reduces maintenance costs. Cladding can be powder coated from any colour in the classic RAL range.

FURTHER OPTIONS

- Custom-made angled shapes are available to suit your design
- Mullions and transoms
- Multi-sash and combination windows (fixed and opening lights) all in one frame are also available
- Factory pre-finished to any colour from the classic RAL range

AVAILABLE SIZES

Min width	238 mm
Max width	2988 mm
Min height	238 mm
Max height	2988 mm
Max width + height	5000 mm

NOTE: Size limitations also depend on the weight of the glazing, for further information please contact your nearest NorDan office.